



Gravel, all-road or whatever you want to call it, the Grade is built for adventure, right out of the box. With a new, leaner look, a purposeful redesign of our iconic Triple Triangle[™], and engineered to take you and your ride further and faster, the Grade is more compliant, versatile, and adjustable than ever before.

Key Features



Floating Stays

All-day rideability

More vertical compliance on both aluminum and carbon models than previous generation of Grade for a more comfortable time in the saddle, no matter the terrain.



Flip Chip Fork

Race ready or long and steady

The top two model Grades are equipped with a flip chip fork to provide 15 mm of adjustability. This allows riders to go from 55 mm to 70 mm of fork offset. Run the 55 mm offset for gravel races or flip to the "lowtrail" 70 mm offset when you're loaded up with cargo on a bikepacking adventure.

DFD - Dual Fiber Dynamics (Carbon Models) More control and less fatigue

The Grade's seat stays are comprised of two lightweight fibers: a tough composite of carbon and fiberglass. The solid fiberglass core provides toughness and damping, and the carbon fiber outer layers act to control stiffness. In the end, you have a bike that gives the rider a lot more control and less fatigue on the ride.

Smart Routing (Carbon Models)

Internal Di2 routing and dropper post compatible with stealth routing.

Removable Fender Bridge (Carbon Models) Keep the skid marks on the trail.







The Abilities



Adapter: 140mm UP

Adapter: 160mm UP

Spacers: 15mm

Spacers: 15mm

160mm rotor

180mm rotor

Rearward axle position Forward axle position

Adapter: 140mm UP

Adapter: 160mm UP

Spacers: none

180

Spacers: none

Serviceability

External Cable Routing for easy access and maintenance.

No need to disconnect hydraulic lines to re-bleed them.

Adjustability —

Flatmount Brakes

Out of the box with native 160mm rotors front / rear on the Carbon Grade. With a standard adapter, the Grade Carbon can move up to 180mm rotors. This gives big braking power for when your loaded down with lots of gear or charging into the rough.

Grade Alloy is native 140 rear and 160mm front.



Mounting Points Galore

All the frame and fork mounts for all the bags and bottles you need for a long tour. The Grade comes with top tube feed bag bosses and fork leg "anything cage" bosses. The alloy frame even has bottle bosses on the Seat Stays, that's pretty unique!



Tire Clearance All Grades are spec'd with 37c width tires, but can easily accomodate up to 42mm measured clearance

Mudguards – rear accepts full-length fender



Standard Interfaces No proprietary components




Stealth Dropper post compatible.

– Compatibility –



R&D and Geometry



Grade Carbon/Alloy

| IZES eat Tube Length op Tube Horizontal op Tube Actual ead Tube Angle eat Tube Angle tandover ead Tube Length | 44* 42.0 53.1 50.8 69.0° 73.0° 70.0 | 48 45.7 54.5 52.3 70.5° 73.0° | 51 49.4 55.9 53.8 70.5° 73.0° | 55 53.1 57.4 55.5 72.3° 73.0° | 58 56.8 58.7 57.1 72.3° | 61 60.5 60.2 58.8 72.3° |
|--|--|--|--|---|---|--|
| op Tube Horizontal op Tube Actual ead Tube Angle eat Tube Angle tandover | 53.1 50.8 69.0° 73.0° | 54.5 52.3 70.5° 73.0° | 55.9 53.8 70.5° | 57.4 55.5 72.3° | 58.7 57.1 72.3° | 60.2 58.8 |
| pp Tube Actual ead Tube Angle eat Tube Angle tandover | 50.8 69.0° 73.0° | 52.3 70.5° 73.0° | 53.8 70.5° | 55.5 72.3° | 57.1 72.3° | 58.8 |
| ead Tube Angle eat Tube Angle tandover | 69.0° 73.0° | 70.5° 73.0° | 70.5° | 72.3° | 72.3° | |
| eat Tube Angle tandover | 73.0 ° | 73.0° | | | | 72.3° |
| tandover | | | 73.0° | 73.0° | 77.00 | |
| | 70.0 | 1 2 2 | | | 73.0° | 73.0° |
| ead Tube Length | | 73.1 | 76.0 | 79.1 | 82.4 | 85.1 |
| 3 | 10.2 | 11.9 | 14.5 | 16.0 | 18.7 | 21.0 |
| /heelbase | 102.5 | 104.2/ 102.7 | 105.7/ 104.3 | 105.5/ 104.3 | 107/ 105.5 | 108.5/ 107 |
| ront Center | 60.6 | 60.8 | 62.3 | 62.1 | 63.4 | 65.0 |
| hain Stay Length | 43 | 44.5/ 43 | 44.5/ 43 | 44.5/ 43 | 44.5/ 43 | 44.5/ 43 |
| ottom Bracket Drop | 7.5 | 7.5 | 7.3 | 7.3 | 7.0 | 7.0 |
| ottom Bracket Height | 27.6 | 27.6 | 27.9 | 27.9 | 28.1 | 28.1 |
| ork Rake | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| rail | 7.9 | 6.9 | 6.9 | 5.7 | 5.7 | 5.7 |
| tack | 52.4 | 54.6 | 56.8 | 59.0 | 61.2 | 63.4 |
| aaab | 37.0 | 37.8 | 38.5 | 39.4 | 40.0 | 40.8 |
| ra ti | nain Stay Length httom Bracket Drop httom Bracket Height rk Rake ail | hain Stay Length43ottom Bracket Drop7.5ottom Bracket Height27.6rk Rake5.5ail7.9ack52.4 | 43 44.5/43 ottom Bracket Drop 7.5 ottom Bracket Height 27.6 rk Rake 5.5 ail 7.9 ack 52.4 | 43 44.5/43 44.5/43 bittom Bracket Drop 7.5 7.5 7.3 bittom Bracket Height 27.6 27.9 rk Rake 5.5 5.5 5.5 ail 7.9 6.9 6.9 ack 52.4 54.6 56.8 | 43 44.5/43 44.5/43 44.5/43 bittom Bracket Drop 7.5 7.5 7.3 bittom Bracket Height 27.6 27.9 27.9 rk Rake 5.5 5.5 5.5 ail 7.9 6.9 6.9 ack 52.4 54.6 56.8 59.0 | A344.5/4344.5/4344.5/4344.5/43hain Stay Length4344.5/4344.5/4344.5/43httom Bracket Drop7.57.57.37.3httom Bracket Height27.627.627.928.1httom Bracket Height5.55.55.55.5http://rk Rake5.55.55.55.5ail7.96.96.95.75.7ack52.454.656.859.061.2 |

*Size 44 is only available in alloy



